

# EMG 80 ton power press

<b>State</b>	<b>NEW</b>
<b>Category</b>	Press
<b>Brand</b>	EMG
<b>Model</b>	80T
<b>Serial number</b>	-
<b>Year of manufacture</b>	-
<b>Inventory number</b>	100029



## CHARACTERISTICS

Adjustable stroke : from 8 to 120 mm  
Swan-neck depth : 300 mm  
Shut Height : 400 mm  
Stroke per minute : 100  
Press ram adjustment : from 0 to 100 mm

### Standard equipment

Fixed frame  
6-digit counter with reset switch  
8-digit counter without reset switch  
Automatic lubrication with level control  
Bi-manual push-button safety control  
Stroke-by-stroke or continuous working  
Hydraulic unblocking system of the sliders  
Balancing system for the sliders  
Ejection bar in the press slider

## COMPOSITION AND ACCESSORIES

### Options (non-included)

Automatic vertical shield with pedal control  
SICK safety opto-electronic device : simple and double one  
Pedal control for machine without movable shielding  
Blower cam with magnetic sensor, solenoid valve 3/2 + tap locking valve  
Tilt table frame at 15° (hydraulic jack)  
Additional cam to collect information (feeder control, ...)  
Electronic cams Omron with 8 outlets  
Special selector for outside control (cycle departure outside of the press)  
6-digit counter pre-selector  
Fantini rubber cushion model PA/2ST : 80 mm stroke, 7-ton power with table plug, 80 mm thick, adapted to Fantini cushion, with 4 obrounds & 4 ejectors of 85 mm  
Worktable halogen lighting : 24 V 50 W with 500 mm flex

