

# EMG 45 ton power press

<b>State</b>	<b>NEW</b>
<b>Category</b>	Press
<b>Brand</b>	EMG
<b>Model</b>	45T
<b>Serial number</b>	-
<b>Year of manufacture</b>	-
<b>Inventory number</b>	100028



## CHARACTERISTICS

With electro-pneumatic mono-disc clutch

### Technical data

Adjustable stroke : from 6 to 100 mm  
 Swan-neck depth : 220 mm  
 Shut Height : 350 mm  
 Stroke per minute : 130  
 Press ram adjustment : from 0 to 70 mm

### Standard equipment

Fixed frame  
 6-digit counter with reset switch  
 8-digit counter without reset switch  
 Automatic lubrication with level control  
 Bi-manual push-button safety control  
 Stroke-by-stroke or continuous working  
 Hydraulic unblocking system of the sliders  
 Balancing system for the sliders  
 Ejection bar in the press slider

## COMPOSITION AND ACCESSORIES

### Options (non-included)

Automatic vertical shield with pedal control  
 SICK safety opto-electronic device : simple and double passage  
 Pedal control for machine without movable shielding  
 Blower cam with magnetic sensor, solenoid valve 3/2 + tap locking valve  
 Tilt table frame at 20° (hydraulic jack)  
 Additional cam to collect information (feeder control, ...)  
 Electronic cams Omron with 8 outlets  
 Special selector for outside control (cycle departure outside of the press)  
 6-digit counter pre-selector  
 Fantini rubber cushion model PA/2ST : 60 mm stroke, 3-ton power at 6,5 bars with table plug, 80 mm thick, with 4 obrounds & 4 ejectors of 85 mm  
 Worktable halogen lighting : 50W with 500 mm flex  
 Worktable lighting : 2 neon tubes (18 W, only if Safety Opto-Electronic device)  
 Variable speed drive with selection by potentiometer (380 V Tri)

Set of 2 anvil stakes DIN 508 M14 for T-grooves  
 Set of 4 anti-vibration supports diameter 125 mm  
 Lubricating kit (2 l pneumatic oil + 2 l lubricating oil)  
 Band feeder - Straightener - Decoiler

