

# EMG pneumatic press 4.3T



<b>State</b>	<b>NEW</b>
<b>Category</b>	Press
<b>Brand</b>	EMG
<b>Model</b>	4.3 T
<b>Serial number</b>	-
<b>Year of manufacture</b>	-
<b>Inventory number</b>	100010

## CHARACTERISTICS

Adjustable stroke : from 0 to 40 mm  
Swan-neck depth: 110 mm  
Shut height: 295 mm  
Strokes per minute : 30

### VERSION 1

Machine delivered without any equipment and any control

### VERSION 2

Bi-manual push-button safety control  
Lateral protection panels  
Distributor  
Regulating and lubricating filter  
Machine fixed on to its plinth, connected ready to work

### VERSION 3 Version 2 with :

Pedal control to work protected tool (no risk for the operator)  
Key-control selector  
Machine fixed on to its plinth, connected ready to work

## COMPOSITION AND ACCESSORIES

### Options (non-included)

Base support 450 mm section to let legs through  
Set of 2 lateral panels, dimensions 350 x 250 (only with based support)  
5-digit counter with reset switch  
Blocking of the press at dead bottom centre (control with the bimanual to go up and down)  
Pause at dead bottom centre  
Excess flow valve for descent speed regulation  
Full set of filter & exhaust pipes to decrease level noise  
Additional regulator to work with pressure under 3 bar (mini 0.5 bar)  
Power regulator with needle pressure gauge : cycle repetition and 3 % precision  
Power regulator with digital pressure gauge : cycle repetition and 1 % precision  
Set of 2 anvil stakes for T groove M10  
Set of 4 anti-vibration supports ? 46  
Maintenance kit  
ER25 collet holder, with a collet chuck (2 to 16 mm Ø) and key of tightening  
Parts quality system with force and displacement transducer

