

# EMG pneumatic press 4.3T



<b>State</b>	<b>NEW</b>
<b>Category</b>	Press
<b>Brand</b>	EMG
<b>Model</b>	4.3 T
<b>Serial number</b>	-
<b>Year of manufacture</b>	-
<b>Inventory number</b>	100010

## CHARACTERISTICS

Adjustable stroke : from 0 to 40 mm  
 Swan-neck depth: 110 mm  
 Shut height: 295 mm  
 Strokes per minute : 30

### VERSION 1

Machine delivered without any equipment and any control

### VERSION 2

Bi-manual push-button safety control  
 Lateral protection panels  
 Distributor  
 Regulating and lubricating filter  
 Machine fixed on to its plinth, connected ready to work

### VERSION 3 Version 2 with :

Pedal control to work protected tool (no risk for the operator)  
 Key-control selector  
 Machine fixed on to its plinth, connected ready to work

## COMPOSITION AND ACCESSORIES

### Options (non-included)

Base support 450 mm section to let legs through  
 Set of 2 lateral panels, dimensions 350 x 250 (only with based support)  
 5-digit counter with reset switch  
 Blocking of the press at dead bottom centre (control with the bimanual to go up and down)  
 Pause at dead bottom centre  
 Excess flow valve for descent speed regulation  
 Full set of filter & exhaust pipes to decrease level noise  
 Additional regulator to work with pressure under 3 bar (mini 0.5 bar)  
 Power regulator with needle pressure gauge : cycle repetition and 3 % precision  
 Power regulator with digital pressure gauge : cycle repetition and 1 % precision  
 Set of 2 anvil stakes for T groove M10  
 Set of 4 anti-vibration supports ? 46  
 Maintenance kit  
 ER25 collet holder, with a collet chuck (2 to 16 mm Ø) and key of tightening  
 Parts quality system with force and displacement transducer

