

EMG pneumatic press 2T



| | |
|----------------------------|------------|
| State | NEW |
| Category | Press |
| Brand | EMG |
| Model | 2T |
| Serial number | - |
| Year of manufacture | - |
| Inventory number | 100005 |

CHARACTERISTICS

Adjustable stroke : from 0 to 69 mm
 Swan-neck depth: 110 mm
 Shut height : 200 mm
 Strokes per minute : 30

VERSION 1

Machine delivered without any equipment and any control

VERSION 2

Bi-manual push-button safety control
 Lateral protection panels
 Distributor
 Regulating and lubricating filter
 Machine fixed on to its plinth, connected ready to work

VERSION 3 Version 2 with :

Pedal control to work protected tool (no risk for the operator)
 Key-control selector
 Machine fixed on to its plinth, connected ready to work

COMPOSITION AND ACCESSORIES

Options (non-included)

Base support 450 mm section to let legs through
 Set of 2 lateral panels, dimensions 350 x 250 (only with based support)
 5-digit counter with reset switch
 Blocking of the press at dead bottom centre (control with the bimanual to go up and down)
 Pause at dead bottom centre
 Excess flow valve for descent speed regulation
 Full set of filter & exhaust pipes to decrease level noise
 Additional regulator to work with pressure under 3 bar (mini 0.5 bar)
 Power regulator with needle pressure gauge : cycle repetition and 3 % precision
 Power regulator with digital pressure gauge : cycle repetition and 1 % precision
 Set of 2 anvil stakes for T groove M10
 Set of 4 anti-vibration supports ? 46
 Maintenance kit
 ER25 collet holder, with a collet chuck (2 to 16 mm Ø) and key of tightening
 Parts quality system with force and displacement transducer

